

COMING SOON

Robinson R44 Raven II

Milan, Italy



STARTING PRICE	OPENING PRICE	BIDS PLACED	RESERVE PRICE
—	—	0	No

LOT	AUCTION	BRAND	CATEGORY
#179	#150	Robinson	Aircraft
BIDDING CLOSES	SELLER		
—	C*****s		

This document is a snapshot taken at the time and date shown. Prices, bid counts, closing times and availability change continuously. Always confirm the current position on collectairs.com before bidding or making any commitment.

DESCRIPTION

When Frank Robinson set out to build a light four-seat helicopter, the civil rotary market was divided between costly light turbines and underpowered light pistons that lacked true four-seat capacity. The R44 redefined general aviation rotorcraft by delivering 115-knot cruise speeds and four-place utility at a fraction of turbine operating costs. Among the variants, the R44 Raven II stands out as the definitive iteration of the platform, combining fuel-injected horsepower with improved hot-and-high performance that elevated it into the world's best-selling civil helicopter.

Introduced in 2002, the Raven II was Robinson Helicopter Company's answer to operators seeking better payload and high-density-altitude performance without making the financial jump to a turbine engine. By replacing the carbureted powerplant of earlier variants with a fuel-injected Lycoming IO-540-AE1A5, Robinson eliminated carburetor icing concerns and secured a 245-horsepower takeoff rating. Coupled with standard hydraulic flight controls, redesigned main rotor blade tip caps, and a robust 28-volt electrical system, the Raven II proved that piston helicopters could handle serious transport, training, and commercial utility duties day after day.

Quick facts

What makes the Raven II the benchmark four-seat piston helicopter?

The Raven II balances operating economics with genuinely useful performance. Where earlier light piston rotorcraft forced hard choices between fuel quantity and passenger count, the Raven II allows four average-sized adults to cruise at speeds competitive with light twin-engine fixed-wing aircraft while maintaining a practical operating range. The fuel-injected engine ensures precise fuel distribution across all six cylinders, offering smoother operation and cleaner throttle response while eliminating the pilot workload associated with managing carburetor heat in humid or marginal weather conditions.

Additionally, the Raven II's standard hydraulic power steering system transforms flight handling characteristics. By isolating cyclic and collective control feedback, hydraulics significantly reduce pilot fatigue during long cross-country flights or prolonged hover maneuvers. The upgrade to a 28-volt electrical system also opened the door for high-draw modern avionics, advanced flight displays, and factory-installed air conditioning—features once reserved exclusively for multi-million-dollar turbine machinery.

Powerplant, systems and technical highlights

- Fuel-injected six-cylinder Lycoming IO-540-AE1A5 engine, derated to 245 hp for 5-minute takeoff power and 205 hp continuous operation.
- Standard hydraulic flight control system eliminating cyclic and collective feedback forces for smooth, low-effort handling.
- High-inertia two-blade main rotor system with stainless steel skin and aerodynamic tip caps to optimize rotor efficiency and reduce flyover noise.
- 28-volt electrical system providing ample capacity for high-draw avionics packages, landing lights, and optional cabin air conditioning.
- Factory-fitted crashworthy bladder fuel tanks designed to minimize post-impact fuel spillage.
- Tri-hinged underslung main rotor hub designed to minimize hub bending stresses during maneuvering flight.

How it compares

Performance figures and operating specifications for the Bell 206B-3 JetRanger III represent typical values and vary based on installation, operating weight, and atmospheric conditions.

Honest ownership note: Prospective R44 owners must plan around the rigid 12-year/2,200-hour major overhaul cycle mandated by Robinson Helicopter Company. Regardless of whether an airframe reaches 2,200 flight hours

or 12 calendar years first, a comprehensive factory or authorized service center overhaul of the airframe, engine, dynamic components, and rotor blades is required. Pre-purchase inspections should focus closely on main and tail rotor blade condition (checking for blade skin debonding or corrosion), compliance with bladder fuel tank service bulletins, mast nut torque records, and exhaust system integrity. Operators must also respect the specific regulatory requirements of SFAR 73, which mandates specialized initial and recurrent flight training regarding low-G mast bumping precautions and energy management in two-blade teetering rotor systems.

Exterior and cabin

Exterior

- Distinctive teardrop cabin profile designed for aerodynamic efficiency and wide-angle visibility.
- Raised tail boom structure with enclosed driveshaft feeding a high-mounted two-blade tail rotor for ground safety.
- Tubular steel skid landing gear with optional ground handling wheel attachments and available pop-out float configurations.
- Exposed teetering main rotor head assembly with stainless steel droop stops and trim straps for ease of preflight inspection.

Cabin and cockpit

- Four individual individual seats clad in leather or velocity fabric with integrated storage compartments under each seat bottom.
- Signature center T-bar cyclic control stick allowing clear legroom and easily shared or removed dual flight controls.
- Low cabin door sill height providing unobstructed entry and exit for pilot and passengers.
- Unmatched 180-degree forward and lateral field of view through broad acrylic bubble windshields and door windows.

Is the Robinson R44 Raven II right for your mission?

- Private owner-pilots seeking a fast, dependable cross-country machine capable of taking friends or family on real trips.
- Commercial operators and flight schools requiring a proven, cost-effective platform for advanced dual instruction, pipeline patrol, or photo flights.
- Utility and agricultural operators looking for an agile, low-overhead piston platform with solid high-altitude hover performance.

The Robinson R44 Raven II remains the benchmark standard of piston helicopter design, effectively bridging the gap between light two-seat trainers and complex turbine platforms. By combining fuel injection, hydraulic controls, and reliable cruise speeds inside a practical, uncluttered airframe, it offers impressive mission versatility per aviation dollar. For operators who respect its maintenance schedule and operating characteristics, the Raven II provides an exceptionally capable, liquidity-proven rotary-wing asset.

SPECIFICATIONS

General Information

Model	Robinson R44 Raven II
-------	-----------------------

Engine & Power Systems

Engine Type	Lycoming IO-540-AE1A5
Propeller Type	Two-blade main and tail rotor system

Avionics & Equipment

Avionics	Standard VFR panel with optional Garmin GTN glass flight deck integration
----------	---

PHOTOGRAPHS

3 of 4 photographs reproduced here. The complete gallery is on the listing page.

EXTERIOR





INTERIOR



HOW TO BID ON THIS LOT

Bidding is online at CollectAirs. Register and complete verification in good time before the lot closes, verification is reviewed by our team rather than granted instantly.

collectairs.com/auctions/robinson-r44-raven-ii

Questions about this aircraft, the paperwork or the process can be sent to our team at any hour on WhatsApp, or by email at info@collectairs.com.

OTHER LIVE AUCTIONS

Live when this document was prepared. Stages and availability change: check the site for the current position.



AERO DESIGN PULSAR XP100

Bad Vöslau, Austria

€20,000 CURRENT PRICE

Closes 8 October 2026, 13:00 UTC



Ikarus Comco C42

Kirn, Germany

€65,000 CURRENT PRICE

Closes 8 October 2026, 19:00 UTC



Rare UTVA AERO 3

Büren, Germany

€20,000 CURRENT PRICE

Closes 8 October 2026, 19:00 UTC



Robin HR 100 210D

Nordhorn, Germany

€49,000 CURRENT PRICE

Closes 15 October 2026, 19:00 UTC

Every lot above opens its own page. Browse all live lots at collectairs.com/auctions/live

IMPORTANT INFORMATION

Closing times can change

The closing time shown is indicative. Auctions may be extended automatically when bids arrive close to the deadline, and CollectAirs may reschedule, pause or withdraw a lot at any time. The time shown on the website governs.

Prices are indicative

Starting prices, current bids and any reserve are subject to change and may be corrected, revised or withdrawn. Where a lot carries a reserve, the amount is confidential and the lot will not sell below it. Figures here exclude applicable fees, taxes, duties, transport and registration costs.

No offer and no contract

This document is provided for information only. It is not an offer, a valuation, an appraisal, or an invitation to treat, and it forms no part of any contract. Bidding and sale are governed solely by the CollectAirs Terms and Conditions in force at the time of the auction.

Condition and airworthiness

Aircraft are sold as they stand. Descriptions, specifications, hours, dates and maintenance status are supplied by the seller and, while CollectAirs curates and verifies listings, they are not warranted as complete or accurate. Buyers are expected to carry out their own inspection, records review and pre-purchase survey before bidding.

Export, registration and compliance

Deregistration, export, import, customs, tax and re-registration are the buyer's responsibility, as is confirming that the aircraft can be lawfully imported and operated in the intended jurisdiction. Requirements vary by country and can affect both cost and timescale.

Photography and written content

Photographs are supplied by the seller and may have been edited for exposure, colour, straightening or the removal of background distractions, in some cases with AI-assisted tools. Parts of the written description and specification summaries may also have been drafted or edited with AI assistance for clarity and consistency. Such enhancements are made to present the aircraft clearly and are not intended to conceal, add or alter any physical feature, damage or defect. Photographs are illustrative, treat the aircraft itself, and its records, as the only authority on condition.

Seller identity

Seller names are shown in the partially masked form used across the platform. Full counterparty details are exchanged through CollectAirs once an auction concludes.

This document is a snapshot taken at the time and date shown. Prices, bid counts, closing times and availability change continuously. Always confirm the current position on collectairs.com before bidding or making any commitment.